

































CASCADe
LUXURY VINYL

IMPACT
LUXURY VINYL TILE



 <p>IMP01 Fifth Ave Spice</p>	 <p>IMP02 Electric Grey</p>	 <p>IMP03 Ocean Sand</p>	 <p>IMP04 Park Ave Slate</p>	 <p>IMP09 Rodeo Mist</p>
 <p>IMP10 Sunset Khaki</p>	 <p>IMP66 Cathedral Brown</p>	 <p>IMP12 Wall St Steel</p>	 <p>IMP14 Hyde Park Brown</p>	 <p>IMP17 Camben St Tan</p>
 <p>IMP26 Bedrock</p>	 <p>IMP27 Arctic Express</p>	 <p>IMP20 Canal St Fawn</p>	 <p>IMP22 Victoria Grey</p>	 <p>IMP56 Roasted Truffle</p>
 <p>IMP28 Frosted Grey</p>	 <p>IMP50 Duke St Wash</p>	 <p>IMP55 Iron Wood</p>	 <p>IMP65 Horse Shoe Beige</p>	 <p>IMPT71 Ashford Marble</p>
 <p>IMP85 Sandalwood</p>	 <p>IMP67 Wolf Grey</p>	 <p>IMP69 Lighthouse Oak</p>	 <p>IMPT72 Harbour Stone</p>	 <p>IMPT73 Carbon Concrete</p>
 <p>IMPT74 Urban Slab</p>	 <p>IMP80 Cabana Natural</p>	 <p>IMP81 Earl Grey</p>	 <p>IMP83 Light Latte</p>	 <p>IMP84 Apple Wood</p>



IMPACT SPECIFICATIONS

Constructions	PVC
Thickness	2mm
Wear Layer	0.3mm 12 mil
Size	7" x 48" / 12.36" x 24.6"
Finish	Polyurethane w/ anti bacterial nano silver, satin gloss
Edge Detail	Square edge
Sf Per Carton	12.36" x 24.6" = 52.81" 7" x 48" = 51.33
Sf Per Pallet	12.36" x 24.6" = 24.6" = 2,746.12 7" x 48" = 3,079.80
Installation	Glue Down
Classification	Good
Residential Warranty	25 Year Limited Residential
Commercial Warranty	10 Year Limited Medium Commercial
Recommended Adhesive	Cascade XT360
Approved Adhesives	Wolf Grip Premium, Armstrong S - 995.
Emissions	FloorScore Certified

PERFORMANCE TESTING

Fire Rating	ASTM E84 75 or less
Mekel Burner Test	Pass
Heat Stability	KSM 3802 0.3mm/ 0.01"80C+2C, 6hr/1hr
Abrasion Resistance	ASTM D3884 0.1% Loss
Slip Resistance ADA	Exceeds ADA Requirements
Dry Static Coefficient Of Friction	ASTM C1028 0.72
Wet Static Coefficient Of Friction	ASTM C1028 0.67
Residual Indentation	EN 433 ≤ 0.10mm
Color Fastness	ISO 105-B02 ≥ 6
Dimensional Stability	EN 434 ≤ 0.10mm
Flexibility	EN 435 No crack was found
Electrical Behavior	EN 1081 Pass

IMPACT
LUXURY VINYL TILE

